

Johannes VAN LITH et al.

sub
BS
A1
conf

--9. (Amended) A driving belt according to claim 1,
characterised in that edges of the transverse element (4) have been
deburred and/or been rounded by means of a tumbling operation.--

Claims 3-9 were amended to correct multiple
dependency. Attached hereto is a marked-up version of the
changes made to the claims by the current amendment. The
attached page is captioned "VERSION WITH MARKINGS TO SHOW
CHANGES MADE".

Respectfully submitted,

YOUNG & THOMPSON

By

Benoît Castel

Benoît Castel
Attorney for Applicant
Customer No. 000466
Registration No. 35,041
745 South 23rd Street
Arlington, VA 22202
703/521-2297

June 19, 2001

"VERSION WITH MARKINGS TO SHOW CHANGES MADE"

Please amend claims 3-9 as follows:

3. (Amended) A driving belt according to ~~any one of the preceding claims~~ claim 1, characterised in that said projection (14) and said recess (15) are mainly present in the second part (12) of the transverse element (4).

4. (Amended) A driving belt according to ~~any one of the preceding claims~~ claim 1, characterised in that said projection (14) and said recess (15) extend in transverse direction over the entire area of the transverse element between the two recesses (7, 8).

5. (Amended) A driving belt according to ~~any one of the preceding claims~~ claim 1, characterised in that said projection (14) is disposed some distance above the tilting line (18), which distance is smaller than the smallest vertical dimension (A) of the recess (7, 8).

6. (Amended) A driving belt according to ~~any one of the preceding claims~~ claim 1, characterised in that the surface of the projection (14) and of the recess (15) comprises parts (16, 17) which extend at an angle to a horizontal line in the plane in which the band packages (5, 6) lie, and which extends perpendicularly to the direction of the driving belt (1).

7. (Amended) A driving belt according to ~~any one of the preceding claims~~ claim 1, characterised in that said third part (13) of the transverse element (4) comprises parts (16, 17) which extend at an angle to a horizontal line in the plane in which the band packages (5, 6) lie, and which extends perpendicularly to the direction of the driving belt (1).

8. (Amended) A driving belt according to ~~any one of the preceding claims~~ claim 1, characterised in that the transverse element (4) has been made from a strip of material by means of a cutting operation.

9. (Amended) A driving belt according to ~~any one of the preceding claims~~ claim 1, characterised in that edges of the transverse element (4) have been deburred and/or been rounded by means of a tumbling operation.